

Ruote Adottate per Serie 36/2-50/2-50/2FT-75/2L-75/2LFT nelle varie tipologie di Diametri, Battistrada
 Wheels used for 36/2-50/2-50/2FT-75/2L-75/2LFT series in the various types of diameters and tyres

Ruota tipo Wheel type	G	Gd	Gc	GA	GcA	SR	SRd	N	-
Catteristiche del Battistrada Tyre characteristics	Gomma Grigia Grey Rubber			Gomma Conduttiva Nera Conductive Black rubber		Gomma Sintetica Grigia Synthetic Grey rubber		Nylon Nero Black Nylon	
Durezza del Battistrada conforme UNI EN 12527 Tyre hardness in compliance with UNI EN 12527	shore A	76	76	76	85	85	78	78	>100 >
Temperature di Utilizzo Raccomandate Recommended working temperatures	Max+	+40°C	+40°C	+40°C	+40°C	+40°C	+60°C	+60°C	+40°C -
	Min+	0°C	0°C	0°C	-5°C	-5°C	-10°C	-10°C	0°C -
Catteristiche del Nucleo Wheel centre characteristics	Nylon Nero Black Nylon			Nylon Nero Conduttivo Conductive Black Nylon		Polipropilene Grigio Grey Polypropylene			
Catteristiche del Mozzo Hub characteristics	Foro Liscio Plain Bearing	Tubo Parafilo Tube Threadguard	Cuscinetto a Sfera Parafilo Ball Bearing Threadguard	Foro Liscio Plain Bearing	Cuscinetto a Sfera Parafilo Ball Bearing Threadguard	Foro Liscio Plain Bearing	Tubo Parafilo Tube Threadguard	Foro Liscio Plain Bearing	- - - -
Conducibilita'Elettrica conforme UNI EN 12527 Electric conductivity in compliance with UNI EN 12527	hom Ω			-		-		$\frac{m}{kg}$ = Peso per 1 pezzo $\frac{m}{kg}$ = Weight for a piece	
Portata Dinamica conforme UNI EN 12527 Dynamic load capacity conform UNI EN 12527	$\frac{m}{kg}$ D			Resistenza al Rotolamento (FR) alla Portata Nominale Rolling resistance (FR) at rated capacity		$\frac{m}{kg}$ FR			
Portata Statica conforme UNI EN 12527 Static load capacity conform UNI EN 12527	$\frac{m}{kg}$ S			Resistenza al Superamento Ostacolo (FO) alla Portata Nominale Obstacle overcoming resistance (FO) at rated capacity		H ostacolo=1% ϕ della Ruota Min 0.5 mm		$\frac{m}{kg}$ FO	

ITEM	50LG	50LGd	50LGc	50LGA	50LGC	50LSR	50LSRd	50LN
A	-	-	-	-	-	-	-	-
D	-	-	-	-	-	-	-	-
S	-	-	-	-	-	-	-	-
FR	-	-	-	-	-	-	-	-
FO	-	-	-	-	-	-	-	-
	45 X2	53 X2	74 X2	-	-	-	-	34
Code								
ITEM	75LG	75LGd						75LN
A	-	-						-
D	-	-						-
S	-	-						-
FR	-	-						-
FO	-	-						-
	77 X2	85 X2						34 X2
Code								

ITEM	50/L/G-Gd-Gc	75/L/G-Gd
	Nucleo Grigio Grey Centre	Nucleo Grigio Grey Centre