

Requisiti Ruote Serie L nelle varie tipologie di: Diametri, Battistrada, Organi di Rotolamento  
 L series wheels Requirements in the various types of: Diameter, Tyres, Rolling parts

Ruota tipo Wheel type	G	Gd	Gc	SR	SRd	N	Nd	NdRa		
Catteristiche del Battistrada Tyre characteristics	Gomma Rubber	Gomma Rubber	Gomma Rubber	Gomma Sintetica Synthetic Rubber	Nylon	Nylon	Nylon	Nylon		
Durezza del Battistrada conforme UNI EN 12527 Tyre hardness in compliance with UNI EN 12527	shore A 76	76	76	78	>100	>100	>100			
Temperature di Utilizzo Raccomandate Recommended working temperatures	Max- +40°C Min- 0°C	+40°C 0°C	+40°C 0°C	+60°C -10°C	+40°C 0°C	+40°C 0°C	+40°C 0°C		= Peso per 1 pezzo = Weight for a piece	
Catteristiche del Nucleo Wheel centre characteristics	Nylon	Nylon	Nylon	Polipropilene Polypropylene	Nylon	Nylon	Nylon	Nylon		
Catteristiche del Mozzo Hub characteristics	Foro Liscio Plain Bearing	Tubo Parafilo Tube Threadguard	Cuscinetto a Sfera Parafilo Ball Bearing Threadguard	Foro Liscio Plain Bearing	Foro Liscio Plain Bearing	Tubo Parafilo Tube Threadguard	Tubo Parafilo Tube Threadguard			
Portata Dinamica conforme UNI EN 12527 Dynamic load capacity conform UNI EN 12527	D			Resistenza al Rotolamento (FR) alla Portata Nominale  FR						
Portata Statica conforme UNI EN 12527 Static load capacity conform UNI EN 12527	S			Resistenza al Superamento Ostacolo (FO) alla Portata Nominale H ostacolo=1% Ø della Ruota Min 0.5 mm  FO						
ITEM									ITEM	
A						40LN			A	30LN
D						40			D	30
S						28			S	20
FR						42			FR	30
FO						1.6			FO	0.6
						7.3				5.2
€						16			€	-
ITEM						45LN			ITEM	36LSR 36LN
A						45			A	36 36
D						30			D	30 25
S						45			S	45 35
FR						1.5			FR	0.6 1.0
FO						6.3			FO	3.5 5.4
						22				14 12
€	-	-	-	-	-	-	-	-	€	- -
ITEM	50LG	50LGd	50LGc	50LSR	50LSRd	50LN	50LNd			
A	50	50	50	50	50	50	50			
D	30	30	30	30	30	30	30			
S	45	45	45	45	45	45	45			
FR	2.7	2.7	2.7	1.5	1.5	1.4	1.4			
FO	4.0	4.0	4.0	4.5	4.5	6.0	6.0			
	45	53	74	20	28	17	25			
€	-	-	-	-	-	-	-			
ITEM	60LG	-	-	-	-	60LN	60LNd	60LNdRa		
A	60	-	-	-	-	60	60	60		
D	32	-	-	-	-	32	32	32		
S	45	-	-	-	-	45	45	45		
FR	2.45	-	-	-	-	1.37	1.37	1.37		
FO	4.0	-	-	-	-	6.0	6.0	6.0		
	60	-	-	-	-	25	43	35		
€	-	-	-	-	-	-	-	-		
ITEM	75LG	75LGd	-	75LSR	-	75LN	-	-		
A	75	75	-	-	-	75	-	-		
D	35	35	-	-	-	35	-	-		
S	50	50	-	-	-	50	-	-		
FR	1.4	1.4	-	-	-	1.0	-	-		
FO	4.0	4.0	-	-	-	6.5	-	-		
	77	85	-	-	-	34	-	-		
€	-	-	-	-	-	-	-	-		
ITEM	50/L/G-Gd-Gc	60/L/G	75/L/G-Gd							
	Nucleo Grigio Grey Centre	Nucleo Grigio Grey Centre	Nucleo Grigio Grey Centre							
+€	-	-	-							