

# Supporti fissi Serie ML per i vari Diametri di Ruote e Gamma di Fissaggi Fixed forks of the ML series for the various wheels diameters and fixings range

Materiale: Lamiera ferro EN 10130  
Trattamento superficiale: Zincatura passivata UNI ISO 2081  
Material: Iron sheet subject to EN 10130  
surface treatment: passivated galvanisation subject to UNI ISO 2081

Portata statica conforme UNI EN 12527 \*  
 Static load capacity conform UNI EN 12527 \*

=Peso per 1 pezzo  
 =Weight for a piece

ITEM	50/ML/SF		60/ML/SF	
H	46		46	
E-F	6.2-6.2	6.2-8.2	6.2-6.2	6.2-8.2
	-		-	
	77		85	
code				

ITEM	50/ML/SFF		60/ML/SFF	
H	46		46	
E-F	6.2-6.2	6.2-8.2	6.2-6.2	6.2-8.2
	-		-	
	98		106	
code				

ITEM	50/ML/SFP5		60/ML/SFP5	
H	46		46	
E-F	6.2-6.2	6.2-8.2	6.2-6.2	6.2-8.2
	-		-	
	123		131	
code	5021			

ITEM	50/ML/SFP5I	
H	46	
E-F	6.2-6.2	6.2-8.2
	-	
	48	
code		

\* La portata statica indicata per i soli supporti corrisponde a 1.5 portata dinamica verificata secondo UNI 12527 montando una ruota in Nylon

\* The static load capacity mentioned for the only forks correspond to 1.5 dynamic load capacity checked according to UNI 12527 assembling with a nylon wheel

ø50-60

